



Good Looks That Last

MATERIAL SAFETY DATA SHEET

MANUFACTURER: SISSONS PAINTS LIMITED

PRODUCT: ANTI FOULING SEAGUARD

I. COMPOSITION / INGREDIENTS

<i>Raw Materials</i>	<i>% by Weight</i>	<i>CAS Number</i>
Pigment	45. Maximum	
Aromatic Hydrocarbon	15 Maximum	
Inert Materials	2 Maximum	

II. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Colour	Red, Blue, Black
Boiling Point Range	134°C – 140°C
Pounds/Gallons	12.0 ± 0.5
Volatile Organic Content (VOC)	408 grms/litre
Flash Point (Setaflash)	40° C



The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.

MSDS No:07/060/01
Page 1 of 3
Rev: 3
Date Issued:2010/08/16



Good Looks That Last

MATERIAL SAFETY DATA SHEET

III. FIRE AND EXPLOSION HAZARD INFORMATION

Flammable Liquid	N/A
Extinguishing Media	In case of fire use Class B extinguishers (Carbon Dioxide, Dry Chemical or Universal aqueous film forming foam).
Usual Fire and Explosion Hazards	Toxic gases may form when product is contacted by flame or hot surfaces.

IV. HEALTH HAZARD INFORMATION

Effects of Overexposure	Vapour and spray mist are harmful if inhaled. Vapour irritates eye, nose and throat. Repeated exposure to high vapour concentrations, may cause irritation of the respiratory system and permanent brain and nervous system damage.
Eye Contact	Causes severe eye irritation.
Skin Contact	May cause moderate skin irritation. May be absorbed through the skin.
If Ingested	Harmful or fatal if swallowed.

V. SPILL OR LEAK PROCEDURES

Steps to be taken if Material is Spilled	Provide maximum ventilation. Only personnel equipped with proper respiratory, skin and eye protection should be permitted in the area. Remove all ignition sources. Take up spilled material with sawdust, vermiculite or other absorbent material and place into containers for disposal.
--	--



ANSA metal
GROUP OF COMPANIES

The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.

MSDS No:07/060/01
Page 2 of 3
Rev: 3
Date Issued:2010/08/16



Good Looks That Last

MATERIAL SAFETY DATA SHEET

VI. SAFE HANDLING AND USE INFORMATION

Respiratory Protection	Do not breathe vapours.
Ventilation	Ensure maximum ventilation.
Protective Gloves	Wear impermeable protective clothing constructed of nitrile, neoprene or Latex rubber significant to cover the entire body.
Eye Protection	Wear chemical type splash goggles or full face shield.
Other Protective Equipment	Clean or discard contaminated clothing and shoes.

VII. OTHER PRECAUTIONS

Precautions to be taken in Handling and Storing	Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flames. Closed containers may explode when exposed to extreme heat.
---	--



The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.

MSDS No:07/060/01
Page 3 of 3
Rev: 3
Date Issued:2010/08/16