



Good Looks That Last

MATERIAL SAFETY DATA SHEET

III. FIRE AND EXPLOSION HAZARD INFORMATION

Flammable Liquid	N/A
Extinguishing Media	Water, foam, Carbon Dioxide or dry powder.
Usual Fire and Explosion Hazards	Aqueous dispersion will not burn. Dried film is combustible

IV. HEALTH HAZARD INFORMATION

Effects of Overexposure:

Inhalation	Irritation of the respiratory tract. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, seek medical assistance immediately.
Eye Contact	Flush immediately with large amounts of water for at least 15 minutes. Seek medical assistance if irritation persists.
Skin Contact	Wash affected areas with soap and water. Remove contaminated clothing. Seek medical assistance if irritation persists.
If Ingested	Consult a physician immediately. Do not induce vomiting.

V. SPILL OR LEAK PROCEDURES

Steps to be taken if Material is Spilled	Remove all sources of ignition (flames, hot surfaces, electrical). Prevent breathing of vapours. Ventilate area. Contain spilled material and remove with inert absorbent non-sparking tools. Store in closed container.
------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.



Good Looks That Last

MATERIAL SAFETY DATA SHEET

VI. SAFE HANDLING AND USE INFORMATION

Respiratory Protection	Do not breathe vapours.
Ventilation	Eliminate all ignition sources.
Protective Gloves	Do not get on skin. Solvent impermeable gloves to prevent skin contact are recommended.
Eye Protection	Do not get in eyes. Solvent resistance safety eye wear with splash guards or side shields is recommended.
Other Protective Equipment	Solvent impermeable clothing and boots to prevent skin contact are recommended.

VII. OTHER PRECAUTIONS

Precautions to be taken in Handling and Storing	Keep away from heat, sparks and flames. Do not smoke. Extinguish all pilot lights and turn off all sources of ignition and all other non-explosion proof electrical equipment. Do not store above 120 ⁰ F or near fire or open flames.:
-------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



ansa metal
GROUP OF COMPANIES

The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.