

# **MATERIAL SAFETY DATA SHEET**

MANUFACTURER: SISSONS PAINTS LIMITED

PRODUCT: AQUA COAT CLEAR

#### I. COMPOSITION / INGREDIENTS

Raw Materials % by Weight CAS Number

Resin (Non- 24.0 - 27.0

Volatile)

Pigment -

Biocide 0.1 - 0.5

Water 15.0 - 20.0

### II. PHYSICAL AND CHEMICAL PROPERTIES

Physical State Liquid

Colour Clear

Boiling Point Range  $100^{\circ}\text{C} - 200^{\circ}\text{C}$ 

Pounds/Gallons  $9.0 \pm 0.5$ 

Volatile Organic Content (VOC) 30.0 grm/litre

pH 9-11



The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.



## MATERIAL SAFETY DATA SHEET

#### III. FIRE AND EXPLOSION HAZARD INFORMATION

Flammable Liquid N/A

Extinguishing Media Water, foam, Carbon Dioxide or dry powder.

Usual Fire and Explosion Hazards Aqueous dispersion will not burn. Dried film is combustible

Flash Point N/A

#### IV. HEALTH HAZARD INFORMATION

Effects of Overexposure:

Inhalation Irritation of the respiratory tract. If you experience difficulty

in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, summon medical assistance

immediately.

Eye Contact Flush immediately with large amounts of water for at least

15 minutes. Seek medical assistance if irritation persists.

Skin Contact Wash affected areas with soap and water. Remove

contaminated clothing. Get medical assistance if irritation

persists.

If Ingested Consult a physician immediately. Do not induce vomiting.

#### V. SPILL OR LEAK PROCEDURES

Steps to be taken if Material is

Spilled

Remove all sources of ignition (flames, hot surfaces, electrical). Prevent breathing of vapours. Ventilate area. Contain spilled material and remove with inert absorbent

non-sparking tools. Store in closed container.



The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.



# MATERIAL SAFETY DATA SHEET

#### VI. SAFE HANDLING AND USE INFORMATION

Respiratory Protection Do not breathe vapours.

Ventilation Eliminate all ignition sources.

Protective Gloves Do not get on skin. Solvent impermeable gloves to prevent

skin contact are recommended.

Eye Protection Do not get in eyes. Solvent resistance safety eye wear

with splash guards or side shields is recommended.

Other Protective Equipment Solvent impermeable clothing and boots to prevent skin

contact are recommended.

### VII. OTHER PRECAUTIONS

Precautions to be taken in Handling

and Storing

Keep away from heat, sparks and flames. Do not smoke. Extinguish all pilot lights and turn off all sources of ignition and all other non-explosion proof electrical equipment. Do not store above 120°F or near fire or open flames.



The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.