



Good Looks That Last

MATERIAL SAFETY DATA SHEET

MANUFACTURER: SISSONS PAINTS LIMITED

PRODUCT: **BIOCIDAL SOLUTION**

I. COMPOSITION / INGREDIENTS

<i>Raw Materials</i>	<i>% By Weight</i>	<i>CAS Number</i>
Water	< 95.0	
Biocidal Product	< 6.0	Mixture (63449-41-2,67-63-0,90-43-7)

II. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Colour	Clear – Pale Yellow
Boiling Point Range	Approximately 100°C
Pounds/Gallons	8.4 ± 0.5
Flash Point (Setaflash)	N/A
Solubility	Fully miscible in water



ANSA METAL
GROUP OF COMPANIES

The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.

MSDS No: 10/063/01
Page 1 of 3
Rev: 2
Date Issued:2010/08/17



Good Looks That Last

MATERIAL SAFETY DATA SHEET

III. FIRE AND EXPLOSION HAZARD INFORMATION

Flammable Liquid	N/A
Extinguishing Media	Water, Foam, Dry Powder or Carbon Dioxide. This product should not burn due to quantity of water.
Usual Fire and Explosion Hazards	Formation of toxic gases, eg. Carbon Monoxide, Nitrogen Oxides may be released during heating or in case of fire. Keep container tightly closed. Isolate from heat, electrical equipment, sparks and flame.

IV. HEALTH HAZARD INFORMATION

Hazard Designation	Corrosive
Inhalation	Irritation of the respiratory tract. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, seek medical assistance immediately.
Eye Contact	Flush immediately with large amounts of water for at least 15 minutes. Seek medical assistance if irritation persists.
Skin Contact	Remove contaminated clothing immediately. Wash affected areas with soap and water. Seek medical assistance if irritation persists.
If Ingested	Rinse mouth out with a large amount of water, then drink water. Consult a physician immediately. Do not induce vomiting.
Effects of Overexposure	Mild irritation of eyes, skin and mucous membranes is possible in poorly ventilated areas.



ANSA McAL
GROUP OF COMPANIES

The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.

MSDS No: 10/063/01
Page 2 of 3
Rev: 2
Date Issued:2010/08/17



Good Looks That Last

MATERIAL SAFETY DATA SHEET

V. SPILL OR LEAK PROCEDURES

Steps to be taken if Material is Spilled Prevent breathing of vapours. Ventilate area. Contain spilled material with sand. Remove with inert absorbent, non-sparking tools for disposal, store in a closed container to minimise material entering drainage system as product contains material hazardous to aquatic environment.

VI. SAFE HANDLING AND USE INFORMATION

Respiratory Protection	None required in well-ventilated areas.
Ventilation	Maintain sufficient ventilation.
Protective Gloves	Do not get on skin. The use of solvent impermeable gloves to prevent skin contact is recommended.
Eye Protection	Do not get in eyes. The use of safety eyewear with splash guards or side shields is recommended.
Other Protective Equipment	The use of protective clothing and boots to prevent skin contact are recommended.

VII. OTHER PRECAUTIONS

Precautions to be taken in Handling and Storing Handle with care. Do not smoke. Do not store above 30°C
Protect from heat and direct sunlight.



The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.

MSDS No: 10/063/01
Page 3 of 3
Rev: 2
Date Issued:2010/08/17