



Good Looks That Last

# MATERIAL SAFETY DATA SHEET

MANUFACTURER: SISSONS PAINTS LIMITED  
PRODUCT: CONCRETE PRIMER WHITE

## I. COMPOSITION / INGREDIENTS

<i>Raw Materials</i>	<i>% by Weight</i>	<i>CAS Number</i>
Pigment (TiO <sub>2</sub> )	5.0 - 8.0	
Extender	20.0 -25.0	
Resin (Non-volatile)	2.0 - 4.0	
Biocide	0.1 - 0.4	
Mineral Spirits	0.1 - 0.4	
Water	59.0 - 64.0	
Pinene	0.1 - 0.4	

## II. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Colour	White
Boiling Point Range	Approximately 100 <sup>0</sup> C
Pounds/Gallons	10.30 ± 0.5
Volatile Organic Content (VOC)	7.5 gm/litre
Flash Point (Seta flash)	N/A Aqueous dispersion will not burn. Dried films are combustible.



The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.



Good Looks That Last

## MATERIAL SAFETY DATA SHEET

### III. FIRE AND EXPLOSION HAZARD INFORMATION

Flammable Liquid	1B
Extinguishing Media	In case of fire use carbon dioxide dry chemicals, foam, or other approved method of treating a class b fire.
Usual Fire and Explosion Hazards	Keep container tightly closed. Isolate from, heat, electrical equipment sparks and flame.

---

### IV. HEALTH HAZARD INFORMATION

Effects of Overexposure:

Inhalation	Irritation of the respiratory tract. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, seek medical assistance immediately.
Eye Contact	Flush immediately with large amounts of water for at least 15 minutes. Seek medical assistance if irritation persists.
Skin Contact	Wash affected areas with soap and water. Remove soil clothing. Seek medical assistance if irritation persists.
If Ingested	Consult a physician immediately. Do not induce vomiting.



---

The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.

MSDS No:09/018/09  
Page 2 of 3  
Rev: 3  
Date Issued:2010/08/17



Good Looks That Last

## MATERIAL SAFETY DATA SHEET

### V. SPILL OR LEAK PROCEDURES

Steps to be taken if Material is Spilled      Remove all sources of ignition (flames, hot surfaces, electrical). Prevent breathing of vapours. Ventilate area. Contain spilled material and remove with inert absorbent, non-sparking tools. Store in closed container

---

### VI. SAFE HANDLING AND USE INFORMATION

Respiratory Protection	Do not breathe vapours. Use a NIOSH/MSHA approved cartridge type particulate/vapour respirator or air-supplied mask in confined areas. Proper respiratory selection should be determined by adequately trained personnel.
Ventilation	Avoid breathing mists and vapour. Use in well ventilated area. In confined space, mechanical ventilation may be necessary.
Protective Gloves	Keep away from skin. Skin contact can be minimized by wearing protective gloves such neoprene, rubber, etc and where necessary, impervious clothing and boots. A source of clean water should be available in the work area for flushing eyes and skin.
Eye Protection	Keep away from eyes. Eye contact can be avoided by wearing safety glasses or chemical splash goggles
Other Protective Equipment	The use of solvent impermeable clothing and boots to prevent skin contact are recommended.

---

### VII. OTHER PRECAUTIONS

Precautions to be taken in Handling and Storing	Keep away from heat, sparks and flames. Do not smoke. Extinguish all pilot lights and turn off all sources of ignition and all other non-explosion proof electrical equipment. Do not store above 120 <sup>0</sup> F or near fire or open flames.
-------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



**ansa metal**  
GROUP OF COMPANIES

---

The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.

MSDS No:09/018/09  
Page 3 of 3  
Rev: 3  
Date Issued:2010/08/17