



Good Looks That Last

MATERIAL SAFETY DATA SHEET

MANUFACTURER: SISSONS PAINTS LIMITED

PRODUCT: EPOXY THINNER

I. COMPOSITION / INGREDIENTS

| <i>Raw Materials</i> | <i>% By Weight</i> | <i>CAS Number</i> |
|----------------------|--------------------|-------------------|
| Ketones | 25.0 - 35.0 | |
| N. Butyl Alcohol | 7.0 - 15.0 | |
| Xylene | 33.0 - 37.0 | |
| Solvesso 150 | 22.0 - 30.0 | |

II. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--------------------------------|--------------------|
| Physical State | Liquid |
| Colour | Not Applicable |
| Boiling Point Range | 120 °C – 150 °C |
| Pounds/Gallons | 7.1 |
| Volatile Organic Content (VOC) | 851.85 grm / litre |
| Flash Point (Setaflash) | 27.2°C |



ANSA METAL
GROUP OF COMPANIES

The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.



Good Looks That Last

MATERIAL SAFETY DATA SHEET

III. FIRE AND EXPLOSION HAZARD INFORMATION

| | |
|----------------------------------|---|
| Flammable Liquid | Class 1C |
| Extinguishing Media | In case of fire use CO ₂ dry chemicals, foam, or other approved method of treating a Class B fire. |
| Usual Fire and Explosion Hazards | Keep container tightly closed. Isolate from heat, electrical equipment, sparks and flame. |

IV. HEALTH HAZARD INFORMATION

Effects of Overexposure:

| | |
|--------------|--|
| Inhalation | Irritation of the respiratory tract. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, seek medical assistance immediately. |
| Eye Contact | Flush immediately with large amounts of water for at least 15 minutes. Seek medical assistance if irritation persists. |
| Skin Contact | Wash affected areas with soap and water. Remove soil clothing. Seek medical assistance if irritation persists. |
| If Ingested | Consult a physician immediately. Do not induce vomiting. |

V. SPILL OR LEAK PROCEDURES

| | |
|--|--|
| Steps to be taken if Material is Spilled | Remove all sources of ignition (flames, hot surfaces, electrical). Prevent breathing of vapors. Ventilate area. Contain spilled material and remove with inert absorbent, non-sparking tools. Store in closed container. |
|--|--|



ANSAL
GROUP OF COMPANIES

The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.



Good Looks That Last

MATERIAL SAFETY DATA SHEET

VI. SAFE HANDLING AND USE INFORMATION

Respiratory Protection

Do not breathe vapors. Use a NIOSH/MSHA approved cartridge type particulate/vapor respirator or air-supplied mask in confined areas. Adequately trained personnel should determine proper respiratory selection.

Ventilation

Avoid breathing mists and vapor. Use in well ventilated area. In confined space, mechanical ventilation may be necessary.

Protective Gloves

Keep away from eyes. Eye contact can be avoided by wearing safety glasses or chemical splash goggles

Eye Protection

Keep away from skin. Skin contact can be minimized by wearing protective gloves such neoprene, rubber, etc and where necessary, impervious clothing and boots. A source of clean water should be available in the work area for flushing eyes and skin.



ANSA McAL
GROUP OF COMPANIES

The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.

MSDS No:06/044/05
Page 3 of 3
Rev: 3
Date Issued:2010/08/18