



MATERIAL SAFETY DATA SHEET

III. FIRE AND EXPLOSION HAZARD INFORMATION

| | |
|----------------------------------|---|
| Flammable Liquid | 1B |
| Extinguishing Media | In case of fire use CO ₂ dry chemicals, foam, or other approved method of treating a Class B fire. |
| Usual Fire and Explosion Hazards | Keep container tightly closed. Isolate from, heat, electrical equipment sparks and flame. |

IV. HEALTH HAZARD INFORMATION

Effects of Overexposure:

| | |
|--------------|--|
| Inhalation | Irritation of the respiratory tract. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, seek medical assistance immediately. |
| Eye Contact | Flush immediately with large amounts of water for at least 15 minutes. Seek medical assistance if irritation persists. |
| Skin Contact | Wash affected areas with soap and water. Remove soil clothing. Seek medical assistance if irritation persists. |
| If Ingested | Consult a physician immediately. Do not induce vomiting. |

V. SPILL OR LEAK PROCEDURES

| | |
|--|---|
| Steps to be taken if Material is Spilled | Remove all sources of ignition (flames, hot surfaces, electrical). Prevent breathing of vapours. Ventilate area. Contain spilled material and remove with inert absorbent, non-sparking tools. Store in closed container. |
|--|---|



The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.



Good Looks That Last

MATERIAL SAFETY DATA SHEET

VI. SAFE HANDLING AND USE INFORMATION

| | |
|----------------------------|---|
| Respiratory Protection | Do not breathe vapours. Use a NIOSH/MSHA approved cartridge type particulate/vapour respirator or air-supplied mask in confined areas. Proper respiratory selection should be determined by adequately trained personnel. |
| Ventilation | Avoid breathing mists and vapour. Use in well ventilated area. In confined space, mechanical ventilation may be necessary. |
| Protective Gloves | Keep away from skin. Skin contact can be minimized by wearing protective gloves such neoprene, rubber, etc and where necessary, impervious clothing and boots. A source of clean water should be available in the work area for flushing eyes and skin. |
| Eye Protection | Keep away from eyes. Eye contact can be avoided by wearing safety glasses or chemical splash goggles |
| Other Protective Equipment | The use of solvent impermeable clothing and boots to prevent skin contact are recommended. |

VII. OTHER PRECAUTIONS

| | |
|---|---|
| Precautions to be taken in Handling and Storing | Keep away from heat, sparks and flames. Do not smoke. Extinguish all pilot lights and turn off all sources of ignition and all other non-explosion proof electrical equipment. Do not store above 120 ⁰ F or near fire or open flames. |
|---|---|



The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.