



Good Looks That Last

MATERIAL SAFETY DATA SHEET

MANUFACTURER: SISSONS PAINTS LIMITED

PRODUCT: Q.D. GREY METAL PRIMER

I. COMPOSITION / INGREDIENTS

<i>Raw Materials</i>	<i>% By Weight</i>	<i>CAS Number</i>
Resin (Non-Volatile)	14.0 - 16.0	
Pigment	7.0 - 10.0	
Extender	32.0 - 36.0	
Mineral Spirits	14.0 - 16.0	
Metallic Driers	0.5 - 1.0	

II. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Colour	As per shade card
Boiling Point Range	136 ⁰ C - 142 ⁰ C
Pounds/Gallons	11.5 ± 0.5
Volatile Organic Content (VOC)	459.0 gm/litre.
Flash Point (Seta flash)	25 ⁰ C



ANSA McAL
GROUP OF COMPANIES

The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.

MSDS No:09/018/07
Page 1 of 3
Rev: 3
Date Issued:2010/08/17



Good Looks That Last

MATERIAL SAFETY DATA SHEET

III. FIRE AND EXPLOSION HAZARD INFORMATION

Flammable Liquid	1B
Extinguishing Media	In case of fire use CO ₂ dry chemicals, foam, or other approved method of treating a Class B fire.
Usual Fire and Explosion Hazards	Keep container tightly closed. Isolate from, heat, electrical equipment sparks and flame.

IV. HEALTH HAZARD INFORMATION

Effects of Overexposure:

Inhalation	Irritation of the respiratory tract. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, seek medical assistance immediately.
Eye Contact	Flush immediately with large amounts of water for at least 15 minutes. Seek medical assistance.
Skin Contact	Wash affected areas with soap and water. Remove soil clothing. Seek medical assistance if irritation persists.
If Ingested	Consult a physician immediately. Do not induce vomiting.

V. SPILL OR LEAK PROCEDURES

Steps to be taken if Material is Spilled	Remove all sources of ignition (flames, hot surfaces, electrical). Prevent breathing of vapors. Ventilate area. Contain spilled material and remove with inert absorbent, non-sparking tools. Store in closed container.
--	--



ANSAL
GROUP OF COMPANIES

The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.

MSDS No:09/018/07
Page 2 of 3
Rev: 3
Date Issued:2010/08/17



Good Looks That Last

MATERIAL SAFETY DATA SHEET

VI. SAFE HANDLING AND USE INFORMATION

Respiratory Protection

Do not breathe vapors. Use a NIOSH/MSHA approved cartridge type particulate/vapor respirator or air-supplied mask in confined areas. Proper respiratory selection should be determined by adequately trained personnel.

Ventilation

Avoid breathing mists and vapor. Use in well ventilated area. In confined space, mechanical ventilation may be necessary.

Protective Gloves

Keep away from eyes. Eye contact can be avoided by wearing safety glasses or chemical splash goggles

Eye Protection

Keep away from skin. Skin contact can be minimized by wearing protective gloves such neoprene, rubber, etc and where necessary, impervious clothing and boots. A source of clean water should be available in the work area for flushing eyes and skin.

Other Protective Equipment

VII. OTHER PRECAUTIONS

Precautions to be taken in Handling and Storing

Keep away from heat, sparks and flames. Do not smoke. Extinguish all pilot lights and turn off all sources of ignition and all other non-explosion proof electrical equipment. Do not store above 120⁰F or near fire or open flames.



ANSA METAL
GROUP OF COMPANIES

The Information contained herein is given in good faith but no warranty, expressed or implied is made. Sissons Paints would not be liable for any damages, losses or injuries, which may result from the use of or reliance of the information, contained herein. This MSDS is valid for five (5) years.

MSDS No:09/018/07
Page 3 of 3
Rev: 3
Date Issued:2010/08/17