



PDS No: INL 001/18
Date: 12/9/18
Rev:2

SISSONS A.C. LACQUER

PRODUCT DESCRIPTION: A two pack clear lacquer that dries by the action of an acid catalyst. Available in High gloss, Satin or Flat finishes.

RECOMMENDED TYPICAL USES: Suited for application on wood, hard board etc. Ideally suited for use on furniture

ADVANTAGES:

1. Excellent build and flow properties
2. Dries to a hard, tough mar resistant film
3. Excellent heat and water resistance

DIRECTIONS FOR USE: The material is recommended for application on wood, hard-board etc, which have been previously prepared by staining, sealing etc.

Before application, mix by volume 16 parts Lacquer to 1-part catalyst – and agitate thoroughly.
Reduce to spray viscosity.
Good ventilation is recommended
Mix only as required for immediate use i.e. within 4 – 6 hours.
Caution when mixing as catalyst is acid based.

TECHNICAL DATA

PRODUCT REF: INL SERIES

GENERIC TYPE: Urea/Alkyd

COLOUR: N\A

POT LIFE: 8 – 12 Hours

PACK SIZES: 1 US Gallon – catalyst in a separate glass bottle.

SPREADING RATE: Suitable for spray application and for use in automated finishing plants.

FLASH POINT: Below 21 °C

DRYING TIMES: Touch Dry – ½ hour
To re-coat – 4 hours
Hard Dry – 16 hours

APPLICATION METHODS: N\A

THINNER/CLEAN UP: Sissons Industrial Thinners.

SOLIDS BY WEIGHT: 53.10%

SOLIDS BY VOLUME: 51.90%

V.O.C. 210gm/litre

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

ANSA Coatings Limited