



PDS No: PRI 6825
Date: 12/9/18
Rev: 2

SISSONS ALKALI RESISTING PRIMER / SEALER

PRODUCT DESCRIPTION: Based on a high-quality Acrylic Based Emulsion.

RECOMMENDED TYPICAL USES: Specially formulated for use on newly plastered walls, masonry surfaces, concrete etc.

DIRECTIONS FOR USE: Ensure all concrete/masonry surfaces are dry and free of efflorescence. Rub and dust off to remove loose sand etc. Apply, unthinned by brush.

TECHNICAL DATA

PRODUCT REF: PRI 6825

GENERIC TYPE: Aqueous Copolymer

COLOUR: N\A

PACK SIZES: 1 Gallon

SPREADING RATE: 300 – 325 sq. ft/US Gallon

FLASH POINT: N\A

DRYING TIMES: 15-20 minutes. Recoat in 1 hour

APPLICATION METHODS: Brush only

THINNER/CLEAN UP: Use clean water

SOLIDS BY WEIGHT: 43.88%

SOLIDS BY VOLUME: 25.40%

V.O.C.: 4.33 gm / litre

N.B. This Sealer would not prevent blistering of top coats if moisture is present in the substrate.

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

ANSA Coatings Limited