



PDS No: SFP 001/18
Date: 12/9/18
Rev: 2

SISSONS AQUA FLOOR PAINT

PRODUCT DESCRIPTION: A good quality water based acrylic paint with a polished sheen.

RECOMMENDED TYPICAL USES: Suitable for use on concrete, wooden patios, floors etc. where a low odour, high sheen finish is desired.

ADVANTAGES:

1. Quick drying 20 – 30 minutes.
2. Easy to apply.
3. Low odour.
4. Interior/Exterior use.
5. Brushes spills easily cleaned up with water

DIRECTIONS FOR USE:

New Concrete

Surface should be dry and free from loose sand, dust, grease etc. Smooth or trowel clean surfaces must be etched or abraded before a thinned down coat of floor paint is applied. A thin coat is essential for proper penetration and good adhesion. Follow with a second unthinned coat.

Previously painted surfaces

Surface must be free from old flaking paint. This can be achieved by scrapping and wire brushing. Thin paint as above and apply as a sealer. Followed with a second unthinned coat.

New Wood

Surface must be dry and free from dirt and loose particles. Knots must be sealed with sanding sealer. Thin paint as above and apply as a sealer. Followed with a second unthinned coat. Previously painted wooden surfaces, treat as for painted concrete surfaces above.

CLEAN UP: Wash all equipment with clean water immediately after use.

TECHNICAL DATA

PRODUCT REF: SFP SERIES

GENERIC TYPE: Acrylic polymer

COLOUR: Red, Green and Gray

PACK SIZES: ¼ US Gallon. & 1 U.S. Gallon.

SPREADING RATE: 350 – 375 sq. ft. /US Gallon

FLASH POINT: N/A

DRYING TIMES: 20 minutes

APPLICATION METHODS: Brush or roller

THINNER/CLEAN UP: Use clean water

SOLIDS BY WEIGHT: 46.58%

SOLIDS BY VOLUME: 31.13%

V.O.C.: 48.37 gm./litre

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

ANSA Coatings Limited