



PDS No: GYP 001/18
Date: 12/9/18
Rev:2

SISSONS GYPSUM PRIMER/SEALER

PRODUCT DESCRIPTION: A water based textured finish formulated on an acrylic copolymer emulsion, incorporating silica sand. Calcium carbonate as the texturing agent.

RECOMMENDED TYPICAL USES: Ideally suited as a primer / sealer prior to the application of a latex top coat.

ADVANTAGES:

1. Excellent adhesion.
2. Quick drying.
3. Excellent building & penetrating properties.
4. Low water pickup.

DIRECTIONS FOR USE: Surface should be free from loose / powdery materials. Apply one (1) coat of Sissons Gypsum Primer / Sealer and allow to dry. This is followed by one or two coats of Sissons Non-Drip Ceiling White or Sissons Super Matt White to the desired finish

TECHNICAL DATA

PRODUCT REF: GYP 1800

GENERIC TYPE: Acrylic Copolymer

COLOUR: White

PACK SIZES: ¼ US & 1 US Gallon

SPREADING RATE: 350 – 375 ft sq. / US Gallon

FLASH POINT: 113 °F or 45 °C

DRYING TIMES: 15-20mins

APPLICATION METHODS: Brush or roller

THINNER/CLEAN UP: Normally no thinning is required but up to 1 pint of Sissons Paint Thinners may be added to 1 US Gallon of paint.

SOLIDS BY WEIGHT: 51.81%

SOLIDS BY VOLUME: 28.78%

V.O.C.: 336.22 gm / litre

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

ANSA Coatings Limited