



PDS No: VOS 001/18
Date: 12/9/18
Rev:2

SISSONS HI GLOSS VARNISH

PRODUCT DESCRIPTION: A general purpose clear varnish based on top quality alkyd resins.

RECOMMENDED TYPICAL USES: Suitable for any interior wood surface, where a clear finish is desired.

ADVANTAGES:

1. High Gloss.
2. Excellent flow, no brush marks.
3. Maximum durability.
4. High resistance to moisture

DIRECTIONS FOR USE: All dirt, grease and wax must be removed prior to painting, and all surfaces must be dry.

New Surfaces:

Apply two or three coats, allowing 6 – 8 hours drying between coats. In the case of Teak, which is an oily wood, to ensure proper drying, this oil **MUST** be removed by wiping twice with a rag soaked with Sissons Paint Thinners. Allow to dry and follow on in a normal way with clear finish.

Previously Painted Surfaces:

If previous coating is old, remove down to bare wood with Sissons T'soff Paint Remover, ensuring this is completely removed before proceeding as for new work. Sound work can be rubbed down with sandpaper, and then followed with one or two coats of the clear finish as necessary. It is essential to remove completely any wax polish from a surface; otherwise non-drying or slow drying and poor adhesion will result.

TECHNICAL DATA

PRODUCT REF: VOS SERIES

GENERIC TYPE: Long Soybean Oil

COLOUR: Available in clear – glossy only

PACK SIZES: ¼ US Gallon & 1 US Gallon

SPREADING RATE: 375 - 400 sq. ft./US Gallon

FLASH POINT: 113 °F or 45 °C

DRYING TIMES: Touch Dry – 4 hours

Recoat – 12 hours

Hard Dry – 16 hours

APPLICATION METHODS: Brush or spray. For spraying thin with up to ¼ gallon of Sissons Paint Thinner per 1 gallon of varnish

THINNER/CLEAN UP: Sissons Paint Thinner

SOLIDS BY WEIGHT: 51.65%

SOLIDS BY VOLUME: 49.95%

V.O.C.: 445 gm / litre

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

ANSA Coatings Limited