



PDS No: SEP 001/18
Date: 12/9/18
Rev:2

SISSONS NON DRIP CEILING WHITE

PRODUCT DESCRIPTION: Based on an acrylic co-polymer emulsion.

RECOMMENDED TYPICAL USES: Suitable for all interior hardboard, celotex, cement, plaster, gypsum board with appropriate primer and wood surfaces.

ADVANTAGES:

1. Structured to give DRIP-free application.
2. High Opacity
3. Non-Yellowing
4. Excellent resistance to fungus and mildew.

DIRECTIONS FOR USE: Sissons Non-Drip Ceiling White is ready to apply from the can to the cleaned surface. Thinning is not necessary and should be avoided. In its drip free form Sissons Ceiling White will spread smoothly and evenly without thinning over an area as great as that normally covered by a conventional flat Emulsion paint. New or very porous surfaces will need priming. One or two coats should be applied as necessary, allowing 2 – 3 hours drying between coats.

Water stained celotex, hardboard, etc can be redecorated as follows: Repair leaks and allow surface to dry out if done in rainy weather. Fungus / mildew must be removed by wiping with Biocidal Solution. Seal stains with Sissons Universal Undercoat. If stains are very severe, then two coats of “sealer” are recommended. Finish with one full coat of Non-Drip Ceiling Paint and allow to dry.

TECHNICAL DATA

PRODUCT REF: SEP 1835

GENERIC TYPE: Acrylic co-polymer

COLOUR: Available in white only

PACK SIZES: 1 US Gallon & 5 US Gallon

SPREADING RATE: 300-350 sq. ft./ US Gallon

FLASH POINT: N/A

DRYING TIMES: 20-30 mins

APPLICATION METHODS: May be applied by brush or roller.

SOLIDS BY WEIGHT: 19.11%

SOLIDS BY VOLUME: 39.52%

V.O.C.: 5.08 gm/litre

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

ANSA Coatings Limited