



PDS No: VOS 002/18
Date: 12/9/18
Rev:2

SISSONS OIL VARNISH STAIN

PRODUCT DESCRIPTION: Based on selected alkyd resins and dye stuff to give a transparent stain

RECOMMENDED TYPICAL USES: Suitable for floors, chairs, furniture and all wood work where a different colour is required and yet a transparent finish is maintained

ADVANTAGES:

1. Minimal lifting of grain.
2. Easy to apply.
3. Excellent penetration, gives good protection and attractive colour.
4. Does not crack or flake.
5. Enhances appearances of natural grain.
6. Varnishes and stains in one application.

DIRECTIONS FOR USE: Before staining, the wood must be thoroughly dry and rubbed to a smooth surface. Apply the stain with a soft brush taking care to avoid overlapping as this will result in darker areas. A heavy coat of stain or a second coat would increase the “darkness” of the stain.

New wood needs 2-3 coats of varnish to give good build and a “finished” look; the oil varnish stain provides the first coat (varnish and stain), hence to finish, light sanding followed by one or two coats of Sissons Polyurethane or Sissons Hi-Gloss Clear is recommended. Gloss, Satin or Flat varnish could be used.

TECHNICAL DATA

PRODUCT REF: VOS SERIES

GENERIC TYPE: Medium Soybean Oil

COLOUR: Available in 5 standard colours

PACK SIZES: ¼ US Gallon & 1 US Gallon

SPREADING RATE: 375 - 400 sq. ft. /US Gallon

FLASH POINT: 113 °F or 45 °C

DRYING TIMES: Touch Dry – 2 hours

APPLICATION METHODS: Ready for use by brush

THINNER/CLEAN UP: Sissons Paint Thinner

SOLIDS BY WEIGHT: 47.60%

SOLIDS BY VOLUME: 43.20%

V.O.C.: 403.60 gm / litre

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

ANSA Coatings Limited