



PDS No: REM 001/18
Date: 12/9/18
Rev:2

SISSONS PENETRATING LIQUID

PRODUCT DESCRIPTION: A clear processed medium which penetrates and binds loose and powdery material.

RECOMMENDED TYPICAL USES: For interior and exterior uses as a pretreatment on surfaces which were previously painted and on surface on which the paint work is cracking, chalking, flaking or in a friable nature.

DIRECTIONS FOR USE: Remove all loose coating by scraping and wire brushing. Dust off with a stiff brush or broom before applying Sissons Penetrating Liquid. The liquid will then bind the remaining loose material to the substrate to provide a firm base for subsequent coats of paint.

TECHNICAL DATA

PRODUCT REF: REM 1813

GENERIC TYPE: Long alkyd oil resin of Soya-bean

COLOUR: N/A

PACK SIZES: ¼ US & 1 US Gallon

SPREADING RATE: 300 sq. ft / US Gallons depending on the porosity of the surface.

FLASH POINT: 113° OR 45 °C

DRYING TIMES: Touch Dry – 2 hours
Recoat time – 12 hours

APPLICATION METHODS: Brush preferably to increase penetration but roller or spray can be used.

THINNER/CLEAN UP: Sissons Paint Thinner

SOLIDS BY WEIGHT: 21.35%

SOLIDS BY VOLUME: 20.49%

V.O.C.: 528 gm / litre

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

ANSA Coatings Limited