



PDS No: SGP 001/18  
Date: 12/9/18  
Rev:2

## SISSONS PRICE BUSTER OIL

**PRODUCT DESCRIPTION:** A good quality alkyd type gloss paint.

**RECOMMENDED TYPICAL USES:** Suitable for the general decoration of all interior and exterior wooden, steel and concrete surfaces

**ADVANTAGES:**

1. Quick drying, dries in 2-3 hours
2. Extremely easy to apply.
3. Economical and durable.
4. Suitable for interior and exterior use.
5. Non-Yellowing.

**DIRECTIONS FOR USE:**

**New Work – Wood**

New surfaces should be clean and dry before priming or sealing is attempted. Treat all knots with 2 thin coats of Sanding Sealer, follow with one coat of Sissons Universal Undercoat, then follow with 2 coats of Sissons Price Buster Oil Paint.

**New Work – Metal**

Remove all rust, dirt, grease, oil etc. Apply one coat of Sissons Zinc Chromate Primer, Or Zinc

Phosphate Primer – White, follow with two coats of Sissons Price Buster Oil Paint.

**Old Work – Wood and Metal**

Previously painted surfaces should be examined for loose and flaking material, which should be removed as necessary. These surfaces should be cleaned and rubbed down and patch primed with the appropriate Sissons Primer before painting.

**Masonry**

For new work, rub down to remove loose material, apply one coat of Sissons Alkali Resisting Primer and follow with 1 or 2 coats of Sissons Price Buster Oil Paint. Old concrete work in sound condition, Sissons Price Buster Oil Paint could be applied straight on, however if surface is glossy then sand lightly before painting.

**TECHNICAL DATA**

**PRODUCT REF:** SGP SERIES

**GENERIC TYPE:** Long Soybean Oil

**COLOUR:** Available in standard colours including Black and White. Also available in a Red Oxide, Middle Green and Bright Red as an anti-corrosive roof paint.

**PACK SIZES:** ¼ US & 1 US Gallon

**SPREADING RATE:** 350-375 sq. ft. /US Gallon depending on surface condition.

**FLASH POINT:** 113 °F or 45 °C

**DRYING TIMES:**

Touch Dry – 2 hours  
Recoat – 8 hours  
Hard Dry – 12 hours

**APPLICATION METHODS:** Brush, roller or spray. For spray application, ¼ Gallon of Sisson Paint Thinners per gallon of paint may be used.

**THINNER/CLEAN UP:** Sissons Paint Thinners.

**SOLIDS BY WEIGHT:** 38.39%

**SOLIDS BY VOLUME:** 28.22%

**V.O.C.:** 290.51 gm / litre

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

**ANSA Coatings Limited**