



PDS No: KEN 001/18
Date: 12/9/18
Rev:2

SISSONS ROLLERTEX

PRODUCT DESCRIPTION: A water based textured finish formulated on an acrylic copolymer emulsion, incorporating silica sand. Calcium carbonate as the texturing agent.

RECOMMENDED TYPICAL USES: Ideally suited for poorly plastered concrete walls, wooden surfaces where a “solid” effect is desired or wherever decoration calls for a soft textured finish.

ADVANTAGES:

1. Touch durable finish.
2. High Opacity.
3. Low sheen.
4. Small cracks can be filled.
5. Several patterns can be achieved, depending on technique and instrument used.

SURFACE PREPARATION: All surfaces should be free from loose sand, debris, dirt, grease etc. Discoloured or dark coloured concrete should be primed with Sissons concrete Primer and wooden surfaces with Sissons Universal Undercoat. If surface is already painted in a dark colour paint, then it is recommended that Concrete Primer or Universal Undercoat be first applied.

TECHNICAL DATA

PRODUCT REF: KEN SERIES

GENERIC TYPE: Emulsion copolymer

COLOUR: White

PACK SIZES: 5 US Gallons

SPREADING RATE: 180 - 225 sq. ft / 5 US Gallon pail

FLASH POINT: N/A

DRYING TIMES: Touch Dry – 30 to 40 minutes
Hard Dry – 24 hours

APPLICATION METHODS: Apply Rollertex to a small area by brush, allow to set for 5-10 minutes. Then roll with a patterned roller to achieve desired pattern.

THINNER/CLEAN UP: Wash all brushes and rollers with clean water immediately after use.

SOLIDS BY WEIGHT: 78.30%

SOLIDS BY VOLUME: 58.34%

V.O.C.: 7.19 gm / litre

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

ANSA Coatings Limited