



PDS No: NCF 002/18
Date: 12/9/18
Rev: 2

SISSONS SANDING SEALER - HIGH VISCOSITY

PRODUCT DESCRIPTION: Clear Nitro Cellulose Sanding Sealer

RECOMMENDED TYPICAL USES: Suitable for use on wood, hardboard, wood veneers, etc. Especially designed for the furniture industry

ADVANTAGES:

1. Extremely fast drying.
2. Good build and flow properties.
3. Easy sanding.
4. Could be modified for electrostatic spray

DIRECTIONS FOR USE: Surface to be sealed should be smooth, and free from all matter such as dust, sand grease etc.

Apply one coat of Sissons Sanding Sealer by brush or spray. For spray application thin with 1 – 1½ qts of Sissons N.C. Lacquer Thinner – per Gallon of Sealer.

TECHNICAL DATA

PRODUCT REF: NCF SERIES

GENERIC TYPE: Modified Nitro Cellulose

COLOUR: Normally supplied as a Clear Finish, but colours could be matched to meet individual requirements.

PACK SIZES: 1 US & 50 US– Gallon Drums

SPREADING RATE: 300-325 sq. ft./US Gallon. Allow approximately 25% for spray loss

FLASH POINT: Below 21°C

DRYING TIMES: To Touch – 5-10 minutes
To Sand – 20-30 minutes

APPLICATION METHODS: Can be applied by standard spraying techniques but also suitable for airless automatic spray.

CAUTION: Material is highly flammable and must not be applied near open flames and must only be used in well ventilated areas.

THINNER/CLEAN UP: Sissons N.C. Thinners

SOLIDS BY WEIGHT: 27%

SOLIDS BY VOLUME:

V.O.C.: 665.46 gm / litre

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

ANSA Coatings Limited