



Good Looks That Last
AN ISO CERTIFIED COMPANY

PDS No: NCF 001/18
Date: 12/9/18
Rev:2

SISSONS SANDING SEALER DIY

PRODUCT DESCRIPTION: Clear Nitro Cellulose Sanding Sealer

RECOMMENDED TYPICAL USES: Suitable for use on wood, hardboard, wood veneers etc. Especially designed for the furniture industry.

ADVANTAGES:

1. Extremely fast drying
2. Good build and flow properties.
3. Easy sanding
4. Could be modified for electrostatic spray.

DIRECTIONS FOR USE: Surface to be sealed should be smooth, and free from all matter such as dust, sand, greases etc.

Apply one coat of Sissons Sanding Sealer by brush or spray. For spray application thin with 1 -1 ½ qt. of Sissons N.C. Lacquer Thinner – per gallon of Sealer. For thinning and clean up – use Sissons N.C. Lacquer Thinner.

TECHNICAL DATA

PRODUCT REF: NCF SERIES

GENERIC TYPE: Modified Nitro Cellulose

COLOUR: Normally supplied as a Clear Finish, but colours could be matched to meet individual requirements.

PACK SIZES: ¼ US &1 US Gallon

SPREADING RATE: 300 – 325 sq. ft/ US Gallon. Allow approximately 25% for spray loss

FLASH POINT: Below 21 °C

DRYING TIMES: To Touch 5-10 minutes
To Sand 20-30 minutes

APPLICATION METHODS: Can be applied by standard spraying techniques but also suitable for airless automatic spray.

THINNER/CLEAN UP: Sissons N.C. Thinners

SOLIDS BY WEIGHT:15%

SOLIDS BY VOLUME:

V.O.C.: 754.46 gm / litre

CAUTION: Material is highly flammable and must not be applied near open flames and must only be used in well-ventilated areas.

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

ANSA Coatings Limited