



PDS No: SSG 001/18
Date: 12/9/18
Rev:2

SISSONS SUPER GLOSS OIL PAINT

PRODUCT DESCRIPTION: Based on a long oil Soya Alkyd, incorporates Zinc Oxide to give maximum exterior durability and excellent resistance to fungus and mildew.

RECOMMENDED TYPICAL USES: Suitable for the general decoration and preservation of all interior and exterior wooden, steel and concrete surfaces

ADVANTAGES:

1. Ease of application.
2. Non-penetration on wood, hence self-priming on wood.
3. Resists fungus and mildew.
4. High initial gloss and excellent gloss retention.
5. White is a brilliant white.

DIRECTIONS FOR USE:

New Work – Wood

New surfaces should be clean and dry before priming or sealing is attempted. Treat all knots with 2 thin coats of Sissons Sanding Sealer.

New Work – Metal

Remove all rust, dirt, grease, oil etc. Apply one coat of Sissons Zinc Chromate Primer and follow with two coats of Sissons Super Gloss Oil Paint, allowing overnight drying between coats.

Old Work – Wood and Metal

Previously painted surfaces should be examined for loose and flaking material, which should be removed as necessary. These surfaces should be cleaned and rubbed down, patch primed with the appropriate Sissons Primer, before painting.

Masonry

For new work, rub down to remove loose material apply one coat of Sissons Alkali Resisting Primer and follow with 1 or 2 coats of Sissons Super Gloss Oil Paint. Old concrete work in sound condition, Sissons Super Gloss Oil Paint could be applied straight on, however if surface is glossy, sand lightly before painting.

TECHNICAL DATA

PRODUCT REF: SSG SERIES

GENERIC TYPE: long oil Soya Alkyd

COLOUR: Available in standard colours plus Black and White.

Semi – Gloss Finishes available on request. Colours also available from Sissons Custom Tinting System.

PACK SIZES: ¼ US & 1 US Gallon

SPREADING RATE: 350-375 sq ft /US Gallon depending on surface condition.

FLASH POINT: 113 °F or 45 °C

DRYING TIMES:

Touch Dry – 4 to 6 hours

Recoat – 18 hours

Hard Dry – 24 hours

APPLICATION METHODS: Brush, roller or spray. For spray application 1-1 ½ pt of Sissons Paint Thinners per 1 Gallon may be used.

THINNER/CLEAN UP: Sissons Paint Thinners

SOLIDS BY WEIGHT: 57.41%

SOLIDS BY VOLUME: 40.58%

V.O.C.: 312.96 gm / litre

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

ANSA Coatings Limited