



Good Looks That Last  
AN ISO CERTIFIED COMPANY

PDS No: U UW 001/18  
Date: 12/9/18  
Rev:2

---

## SISSONS UNIVERSAL UNDERCOAT

**PRODUCT DESCRIPTION:** An alkyd based quick drying Undercoat.

**RECOMMENDED TYPICAL USES:** As a base coat for all normal gloss finishes. Can also be used as a Sealer on celotex, hardboard, plyboard etc. on ceilings. Then apply one or two coats of Sissons Non-Drip Ceiling White as necessary.

**ADVANTAGES:**

1. Speed of drying, rapid recoat ability.
2. Superb brush ability and good flow out.
3. High Opacity.
4. Excellent adhesion.
5. Easy to rub down.
6. Provides excellent hold out.
7. Produces a very high build.

**DIRECTIONS FOR USE:** Surfaces to be painted must be dry, clean and free from grease and rust. New or bare work must be primed with the appropriate Sissons Primer.

**TECHNICAL DATA**

**PRODUCT REF:** U UW 3830

**GENERIC TYPE:** Medium Soybean Oil

**COLOUR:** White only

**PACK SIZES:** ¼ US & 1 US Gallon

**SPREADING RATE:** 350-400 sq. ft./US Gallon

**FLASH POINT:** 113 °F or 45 °C

**DRYING TIMES:** Touch Dry – 2 to 4 hours  
Recoat – 12 hours

**APPLICATION METHODS:** May be applied by brush, roller or spray. For spray application 1 – 1 ½ pts. Sissons Paint Thinners per gallon of paint may be used.

**THINNER/CLEAN UP:** Sissons Paint Thinner

**SOLIDS BY WEIGHT:** 51.81%

**SOLIDS BY VOLUME:** 28.76%

**V.O.C.:** 336.22. gm / litre

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

**ANSA Coatings Limited**