



PDS No: VOS 004/18
Date: 12/9/18
Rev: 2

SISSONS WOODSTAIN

PRODUCT DESCRIPTION: Designed primarily to enhance the character of wood where clarity of colour is required.

RECOMMENDED TYPICAL USES: Can be used on all wooden surfaces where a change in natural colour of the wood is desired.

ADVANTAGES:

1. Will not raise wood grains.
2. Excellent penetration.
3. Fast Drying.
4. Good clarity, would not hide wood grains

DIRECTIONS FOR USE: The surface must be clean, dry and finely sanded. Wax or grease must be completely removed. Shake well before and during use. Apply a uniform coat working across then along the grain of the wood. Allow 2-3 hours to dry then rub well with a dry, clean cloth to remove all surplus dye. Alternatively, the stain can be used to tint sealer to the desired shade. The quantity used will depend on customer's preference. Highly flammable – do not use near fire or flame. Do not store near heat or open flames. Keep container tightly closed

TECHNICAL DATA

PRODUCT REF: VOS SERIES

GENERIC TYPE: Soluble dyes in a blend of Solvents.

COLOUR: Jacobean Dark Oak, American Walnut, Mahogany, Teak, Indian Rosewood, Ebony

PACK SIZES:

SPREADING RATE: 400 - 425 sq. ft./US Gallon depending on type of surface and method of application

FLASH POINT: 118 °F or 48 °C

RECOAT TIMES: 2-3 Hours

APPLICATION METHODS: Can be applied by spray or brush or it can be wiped on.

THINNER/CLEAN UP: No thinning is required. For cleanup, use Sissons Industrial Enamel Thinners

SOLIDS BY WEIGHT: N\A

SOLIDS BY VOLUME: N\A

V.O.C.: 833.09 gm/Litre

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

ANSA Coatings Limited