



PDS No: PRI 003/18
Date: 12/9/18
Rev: 2

SISSONS ZINC CHROMATE PRIMER

PRODUCT DESCRIPTION: Based on a combination of Anticorrosive pigments and alkyd medium.

RECOMMENDED TYPICAL USES: For the painting of all interior and exterior steel surfaces. Can be used on Iron, Galvanize and Aluminum surfaces, after these surfaces have been treated with a mordant solution or Etch Primer

ADVANTAGES:

1. Fast Drying.
2. Has excellent rust inhibiting properties.
3. Exceptionally easy to apply.
4. Excellent recoat ability.

SURFACE PREPARATION: Remove all mill scale, rust and other oxide deposits, dirt and grease. To the clean, dry prepared surface apply one coat of Sissons Zinc Chromate Primer. Where alloys or light metals or Zinc coated galvanize are to be coated, a 1st Primer coat of Sissons One Pack Etch Primer must be used to promote adhesion.

DIRECTIONS FOR USE: These materials are supplied ready for use, however on exterior surfaces in warm, sunny conditions some thinning may be necessary to reduce drag.

TECHNICAL DATA

PRODUCT REF: PRI SERIES

GENERIC TYPE: Medium Soybean Oil

COLOUR: Red or yellow

PACK SIZES: ¼ US & 1 US Gallon, 5 US Gallon on request.

SPREADING RATE: 350 – 400 sq. ft. / US Gallon

FLASH POINT: 113 °F or 45 °C

DRYING TIMES: 16 - 24 hours before recoating

APPLICATION METHODS: Material is supplied ready for use by brush or roller application. It is not advisable to use spray application.

THINNER/CLEAN UP: Sissons Paint Thinner

SOLIDS BY WEIGHT: 65.21%

SOLIDS BY VOLUME: 46.03%

V.O.C.: 459 gm/Litre

CAUTION: This paint contains a toxic pigment. Necessary precautions are to be taken when used. STIR WELL BEFORE USE

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

ANSA Coatings Limited