



PDS No: PRI 001/18
Date: 12/9/18
Rev:2

SISSONS CONCRETE PRIMER

PRODUCT DESCRIPTION: Based on an acrylic co-polymer Resin to ensure a tough and durable primer

RECOMMENDED TYPICAL USES: Suitable for use as a Primer on masonry walls and ceilings. Can also be used as a primer on hard board, celotex, etc.

ADVANTAGES:

1. Tough but flexible finish.
2. Good adhesion and penetration.
3. High opacity.

DIRECTIONS FOR USE: To prepare Sissons Concrete Primer for use, add 1 qt. of clean water per gallon of Primer and mix thoroughly. The new surface must be clean, free of dirt, dust, grease, oil and other debris. Fill all cracks, crevices etc, with an appropriate masonry filler. The purpose of a Primer on new concrete surfaces is to promote penetration of the paint system, satisfy porosity of the surface and to promote adhesion of the top coat. In view of this, the primer must be properly thinned down, and care must be taken to avoid application of "heavy" coat.

TECHNICAL DATA

PRODUCT REF: PRI 6823

GENERIC TYPE: Acrylic co-polymer

COLOUR: White

PACK SIZES: 1 US, 2 US & 5 US Gallon

SPREADING RATE: 375-400 sq. ft/ US Gallon depending on porosity of surface.

FLASH POINT: N/A

DRYING TIMES: Touch Dry: 15-20 minutes

Recoat: 1-1½ hours

APPLICATION METHODS: Brush application is the recommended method

THINNER/CLEAN UP: Use clean water

SOLIDS BY WEIGHT: 34.35%

SOLIDS BY VOLUME: 23.81%

V.O.C.: 4.8 gm / litre

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

ANSA Coatings Limited