



PDS No: SMG 001/18  
Date: 12/9/18  
Rev:2

---

## SISSONS MARINE GLOSS

**PRODUCT DESCRIPTION:** Long oil high viscosity alkyd resin base.

**ADVANTAGES:**

Excellent high gloss.  
Quick drying  
Hard wearing  
Durable  
Suited for painting topside and surfaces above deck level

**DIRECTIONS FOR USE:**

**New Work – Wood**

New surfaces should be clean and dry before priming or sealing is attempted.

**New Work – Metal**

Remove all rust, dirt, grease, oil etc. Apply one coat of Sissons Zinc Chromate Primer and follow with two coats of Sissons Marine Gloss Alkyd Paint, allowing overnight drying between coats.

**New Work- Masonry**

Allow to dry thoroughly then rub down to remove loose material. Apply one thinned coat (3parts paint/1 part thinner) followed by two coats unthinned coats of Sissons Marine Gloss Alkyd Paint, allowing overnight drying between coats.

**TECHNICAL DATA**

**PRODUCT REF:** SMG SERIES

**GENERIC TYPE:** Long oil high viscosity alkyd

**COLOUR:** Available in White, Black, Signal Red

**PACK SIZES:** ¼ US & 1 US Gallon

**SPREADING RATE:** 350-375 sq ft /US Gallon

**FLASH POINT:** 113 °F or 45 °C

**DRYING TIME:** 18 hours

**APPLICATION METHODS:** Brush or spray. For spray application thin with up to 1 pt of Sissons Paint Thinners per US Gallons may be used.

**THINNER/CLEAN UP:** Sissons Paint Thinners

**SOLIDS BY WEIGHT:** 58.20%

**SOLIDS BY VOLUME:** 42.20%

**V.O.C.:** 381.31 gm / litre

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

**ANSA Coatings Limited**