



PDS No: VOS 003/18
Date: 12/9/18
Rev:2

SISSONS POLYURETHANE CLEAR VARNISH (GLOSSY, SATIN, FLAT)

PRODUCT DESCRIPTION: A top quality one-pack Polyurethane Coating based on an exceptional quality Alkyd Resin.

RECOMMENDED TYPICAL USES: For interior structural woodwork, table tops, furniture, and wooden floors. It is also recommended for high class marine work due to its outstanding resistance to the ravages of salt laden atmosphere.

ADVANTAGES:

1. Excellent resistance to alcohol, detergents and mild chemicals.
2. Extremely high gloss and very good gloss retention.
3. Extremely hard and resistant to abrasion.
4. Quick Drying.
5. Completely non-toxic
6. Pale colour

DIRECTIONS FOR USE: All dirt, grease and wax must be removed prior to painting, and all surfaces must be dry.

New Surfaces:

Apply two or three coats, allowing 6 – 8 hours drying between coats. In the case of Teak, which is an oily wood, to ensure proper drying, this oil **MUST** be removed by wiping twice with a rag soaked with Sissons Paint Thinners. Allow to dry and follow on in normal way with clear finish.

Previously Painted Surfaces:

If previous coating is old, remove down to bare wood with Sissons T'soff Paint Remover, ensuring this is completely removed before proceeding as new work. Sound work can be rubbed down with sandpaper, and then followed with one or two coats of the clear finish as necessary.

It is essential to remove completely any wax polish from a surface; otherwise non-drying or slow drying and poor

TECHNICAL DATA

PRODUCT REF: VOS SERIES

GENERIC TYPE: Alkyd polymer

COLOUR: Clear only. Available in Glossy, Satin and Flat

PACK SIZES: ¼ US & 1 US Gallon

SPREADING RATE: 375-400 sq. ft./US Gallon.

FLASH POINT: 113 °F or 45 °C

DRYING TIMES: Touch Dry – 2 hours

Recoat – 8 hours

Hard Dry – 12 hours

APPLICATION METHODS: Brush or spray

THINNER/CLEAN UP: Sissons Paint Thinner

SOLIDS BY WEIGHT: 52.35%

SOLIDS BY VOLUME: 51.39%

V.O.C.: 428 gm / litre

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

ANSA Coatings Limited