



PDS No: RMP 001/18
Date: 12/9/18
Rev:2

SISSONS ROAD MARKING PAINT

CHLORINATED RUBBER

PRODUCT DESCRIPTION: A high opacity paint based on a chlorinated rubber medium

RECOMMENDED TYPICAL USES: For lining roads, airfields, car-parks, playgrounds etc.

ADVANTAGES:

1. Resistant to petrol, oil and chemicals.
2. Excellent adhesion to asphalt, concrete, etc.
3. Quick drying.
4. Hard wearing.
5. Minimizes tar bleeding through.
6. Durable.

DIRECTIONS FOR USE: The surface must be dry and free of all powder, grease and loose material from previous coatings. Apply as thickly as possible with a large unworn brush. Stir well before use.

TECHNICAL DATA

PRODUCT REF: RMP SERIES

GENERIC TYPE: Plasticized Chlorinated Rubber

COLOUR: White and Yellow. Available as a standard quality in which no glass beads have been incorporated and as the reflective type in which the minute glass beads protrude up through the paint film on the road surface, providing reflection of vehicle headlights.

PACK SIZES: 1 US Gallon

SPREADING RATE: 250-300 sq. ft./ US Gallon. This varies considerably according to method of application, type of surface, etc.

FLASH POINT: Below 21 °C

DRYING TIMES: Touch Dry – 10 -15 minutes
Hard Dry – 30 minutes

APPLICATION METHODS: By brush, spray or stencil. Supplied ready for use by brush. For spray application thin with 1 Pint of Sissons 500 Thinner/ US Gallon of paint.

THINNER/CLEAN UP: Sissons Thinner 500

SOLIDS BY WEIGHT: 66.88%

SOLIDS BY VOLUME: 46.53%

V.O.C.: 473 gm / litre

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

ANSA Coatings Limited