



PDS No: REM 1815
Date: 12/9/18
Rev:2

SISSONS T'SOFT PAINT AND VARNISH REMOVER

PRODUCT DESCRIPTION: A blend of extremely strong solvents and thickening agents capable of softening old oil/alkyd paint and varnish films.

RECOMMENDED TYPICAL USES: Suitable for the removal of oil paint and varnish from wood, metal, glass, stone etc.

ADVANTAGES:

1. Very quick acting.
2. Penetrating.
3. Non-flammable.

DIRECTIONS FOR USE: Deposit a thick film by brush. Leave 5-10 minutes. Old coatings can then be stripped with a knife or by scrubbing with a stiff brush. If necessary, repeat this operation to remove all traces of paint. Wash stripped area with clean water. Before painting ensure that surface is completely dry and dewaxed with Paint Thinners.

TECHNICAL DATA

PRODUCT REF: REM 1815

GENERIC TYPE: Solvent Based Thixotropic formula

COLOUR: N/A

PACK SIZES: ¼ US & 1 US Gallon

SPREADING RATE: Dependent on thickness of coating to be removed normally 180-200 sq. ft. / US Gallon

FLASH POINT: Non-flammable

DRYING TIMES: Allow to stand for 10-15 minutes before removing.

APPLICATION METHODS: Brush only

THINNER/CLEAN UP: Water, follow with Sissons Paints Thinners to remove traces of wax.

SOLIDS BY WEIGHT: N/A

SOLIDS BY VOLUME: N/A

V.O.C.: 1.083 gm / litre

CAUTION:

T'soft remover is non-flammable, but operators should avoid smoking as inhaling vapour through a lighted cigarette can cause dizziness.

These recommendation and data are offered in good faith, but without guarantee or warranty, as conditions and methods of use of our products are beyond our control

ANSA Coatings Limited